



Eaton 286528

Eaton Moeller series xPole - PL6 MCB. PL6, 1-pole, tripping characteristic: C, rated current In: 2 A, rated switching capacity IEC/EN 60898-1: 6 kA

General specifications

PRODUCT NAME	Eaton Moeller series xPole - PL6 MCB
CATALOG NUMBER	286528
EAN	4015082865283
PRODUCT LENGTH/DEPTH	85 mm
PRODUCT HEIGHT	73 mm
PRODUCT WIDTH	17.7 mm
PRODUCT WEIGHT	0.12 kg
COMPLIANCES	RoHS conform
MODEL CODE	PL6-C2/1

Dostawa

APPLICATION

- Switchgear for residential and commercial applications
- xPole - Switchgear for residential and commercial applications

NUMBER OF POLES Single-pole

NUMBER OF POLES (TOTAL) 1

NUMBER OF POLES (PROTECTED) 1

TRIPPING CHARACTERISTIC C

RELEASE CHARACTERISTIC C

AMPERAGE RATING 2 A

TYPE

- Miniature circuit breaker
- PL6

Mechaniczne dane techniczne

WIDTH IN NUMBER OF MODULAR SPACINGS 1

BUILT-IN DEPTH 70.5 mm

DEGREE OF PROTECTION IP20

CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN 1 mm²

CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX 25 mm²

CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN 1 mm²

CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX 25 mm²

Elektryczne dane techniczne

VOLTAGE TYPE AC

RATED OPERATIONAL VOLTAGE (UE) - MAX 230 V

RATED INSULATION VOLTAGE (UI) 440 V

RATED IMPULSE WITHSTAND VOLTAGE (UIMP) 4 kV

FREQUENCY RATING - MIN 50 Hz

FREQUENCY RATING - MAX 60 Hz

RATED SWITCHING CAPACITY (IEC/EN 60898-1) 6 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 230 V 6 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60898) AT 400 V 6 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 230 V 0 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2) AT 400 V 0 kA

OVERVOLTAGE CATEGORY III

POLLUTION DEGREE 2

Weryfikacja projektu zgodnie z IEC/EN 61439 - dane techniczne

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 2 A

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT 0 W

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT 1.4 W

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT 0 W

HEAT DISSIPATION CAPACITY 0 W

AMBIENT OPERATING TEMPERATURE - MIN -25 °C

AMBIENT OPERATING TEMPERATURE - MAX 75 °C

Weryfikacja projektu zgodnie z IEC/EN 61439

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Dodatkowe informacje

CURRENT LIMITING CLASS	3
FEATURES	Additional equipment possible
SPECIAL FEATURES	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
USED WITH	Miniature circuit breaker PL6

10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Zasoby

CHARACTERISTIC CURVE	eaton-xpole-mmc4-6-m-mcb-characteristic-curve-002.jpg
DEKLARACJE ZGODNOŚCI	DA-DC-03_PL6
DWG	eaton-xpole-pl6-mcb-dimensions.jpg eaton-xpole-pl6-mcb-3d-drawing-002.jpg
INSTRUKCJE MONTAŻU	eaton-pdd-rcbo-mcb-installations-il019140zu.pdf
KATALOGI	eaton-miniature-circuit-breaker-xpole-pl6-catalog-ca20190212-en-us.pdf eaton-xpole-pl6-mcb-catalog-ca019069en-en-us.pdf
MCAD MODEL	pls_1p.stp pls_1p.dwg
SCHEMATY POŁĄCZEŃ	eaton-xpole-mmc4-6-m-mcb-wiring-diagram-002.jpg

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

Follow us on social media to get the latest product and support information.

