

Specyfikacje

Eaton 259726

Eaton Moeller series NZM - Molded Case Circuit Breaker. Shunt release, 208-240VAC/DC, 1



Zdjęcie jest reprezentatywne

General specifications

PRODUCT NAME	Eaton Moeller series NZM release
CATALOG NUMBER	259726
EAN	4015082597269
PRODUCT LENGTH/DEPTH	37 mm
PRODUCT HEIGHT	66 mm
PRODUCT WIDTH	32 mm
PRODUCT WEIGHT	0.074 kg
COMPLIANCES	IEC UL/CSA RoHS conform
CERTIFICATIONS	CE marking CSA (File No. 22086) UL (Category Control Number DIHS) UL listed CSA (Class No. 1437-01) UL489 UL (File No. E140305) IEC60947 CSA certified CSA-C22.2 No. 5-09
MODEL CODE	NZM1-XA208-250AC/DC



Elektryczne dane techniczne

VOLTAGE TYPE AC/DC

Komunikacyjne dane techniczne

RATED CONTROL 208 V DC

VOLTAGE RATING	0.7 - 1.1 x Us
VOLTAGE RATING AT AC (X US) - MIN	.7
VOLTAGE RATING AT AC (X US) - MAX	1.1
RATED CONTROL VOLTAGE (RELAY CONTACTS)	208 V DC 250 V DC 250 V AC 208 V AC
RATED CONTROL SUPPLY VOLTAGE	208 - 250 V AC/DC
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	250 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	250 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	250 V
FREQUENCY RATING	50 Hz / 60 Hz / 200 Hz / 400 Hz, DC (shunt release)
PICK-UP POWER CONSUMPTION (SHUNT RELEASE)	2.5 VA/W
REACTION TIME	20 ms
MINIMUM COMMAND TIME - MIN	10 ms
MINIMUM COMMAND TIME - MAX	15 ms
ELECTRIC CONNECTION TYPE	Screw connection

Mechaniczne dane techniczne

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	0
CONNECTION TYPE	With terminal block on the left-hand switch side

VOLTAGE (RELAY CONTACTS)	250 V DC 250 V AC 208 V AC
RATED CONTROL SUPPLY VOLTAGE	208 - 250 V AC/DC
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	250 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	250 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	250 V
FREQUENCY RATING	50 Hz / 60 Hz / 200 Hz / 400 Hz, DC (shunt release)
PICK-UP POWER CONSUMPTION (SHUNT RELEASE)	2.5 VA/W
REACTION TIME	20 ms
MINIMUM COMMAND TIME - MIN	10 ms
MINIMUM COMMAND TIME - MAX	15 ms
ELECTRIC CONNECTION TYPE	Screw connection

Zasoby

DWG	123X305 123I522
ECAD MODEL	ETN.NZM1-XA208-250AC_DC
INSTRUKCJE MONTAŻU	eaton-circuit-breaker-nzm1-xa-xahiv-xhiv-xu-xuhiv-il01203002z.pdf
MCAD MODEL	eaton-cadenas-path-paket 3 prio 3-nzm1_xa.3db eaton-cadenas-side view-nzm1_xa_side.pra

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2025 Eaton. Wszelkie
prawa zastrzeżone.

Eaton jest zarejestrowanym
znakiem towarowym.

Wszystkie inne znaki towarowe są
własnością odpowiednich firm.

Follow us on social media to get the latest
product and support information.

