



Zdjęcie jest reprezentatywne



Eaton 276284

Main load disconnect Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 240/415 V, 100 A, 3P

General specifications

PRODUCT NAME	Eaton Moeller series IS Disconnecter
CATALOG NUMBER	276284
EAN	4015082762841
PRODUCT LENGTH/DEPTH	60 mm
PRODUCT HEIGHT	80 mm
PRODUCT WIDTH	53.1 mm
PRODUCT WEIGHT	0.314 kg
COMPLIANCES	RoHS conform
MODEL CODE	IS-100/3

Specyfikacje produktu

TYPE	IS. Main load disconnector switch
APPLICATION	Switchgear for industrial and advanced commercial applications
DEGREE OF PROTECTION	IP40 IP10
TERMINALS	Lift terminal
IMPRINT/INDICATION	Symbol "arrows"
LAMP SOCKET	Other
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-5 °C
BUILT-IN DEPTH	69.5 mm
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	3.9 W
LAMP POWER	0 W
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
AMPERAGE RATING	100 A
COLOR CALOTTE	Other
SWITCH TYPE	Other Off switch
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	2 kA
VOLTAGE TYPE	AC
LAMP TYPE	Other
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	3
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	100 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	415 V
RATED SWITCHING CAPACITY	10 kA
VOLTAGE RATING - MIN	240 V
WIDTH IN NUMBER OF MODULAR SPACINGS	3
NUMBER OF POLES	Three-pole

Zasoby

DEKLARACJE ZGODNOŚCI	DA-DC-03 IS
DWG	eaton-dimensions-mas-is.jpg 122I172
ECAD MODEL	ETN.IS-100_3.edz
SCHEMATY POŁĄCZEŃ	IS_3P

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

