



Zdjęcie jest reprezentatywne

Eaton 276288

Main load disconnect Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 240/415 V, 125 A, 3P

General specifications

PRODUCT NAME	Eaton Moeller series IS Disconnecter
CATALOG NUMBER	276288
EAN	4015082762889
PRODUCT LENGTH/DEPTH	60 mm
PRODUCT HEIGHT	80 mm
PRODUCT WIDTH	53.1 mm
PRODUCT WEIGHT	0.314 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	EN45545-2 IEC 61373
MODEL CODE	IS-125/3

Specyfikacje produktu

TYPE	IS. Main load disconnecter switch
APPLICATION	Switchgear for industrial and advanced commercial applications
DEGREE OF PROTECTION	IP40 IP10
TERMINALS	Lift terminal
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	16.5 W
IMPRINT/INDICATION	Symbol "arrows"
LAMP SOCKET	Other
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-5 °C
BUILT-IN DEPTH	69.5 mm
HEAT DISSIPATION CAPACITY	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	6.2 W
LAMP POWER	0 W
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	3
AMPERAGE RATING	125 A
COLOR CALOTTE	Other
SWITCH TYPE	Other
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	2 kA
VOLTAGE TYPE	AC
LAMP TYPE	Other
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	3
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	125 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	415 V
RATED SWITCHING CAPACITY	10 kA
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0 W
VOLTAGE RATING - MIN	240 V
WIDTH IN NUMBER OF MODULAR SPACINGS	3

Zasoby

DEKLARACJE ZGODNOŚCI	DA-DC-03 IS
DWG	eaton-dimensions-mas-is.jpg 122I172
ECAD MODEL	ETN.IS-125_3.edz
SCHEMATY POŁĄCZEŃ	IS_3P

NUMBER OF POLES

Three-pole

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Wszelkie prawa zastrzeżone.