

MAA2050A10



OTL50-2 grey 2xAl/Cu 1,5-50mm<sup>2</sup> 1500V Universal terminal

OTL50-2 grey 2xAl/Cu 1,5-50mm<sup>2</sup> 1500V Universal terminal

Product code	MAA2050A10
EAN	4744397014061
ETIM Class	EC000897
Product series	Universal terminals OTL
CN8 code	85369010
Unit	pcs
Package size:	54
Net weight	0,071 kg
Net length	0,049 m
Net width	0,03 m
Net depth	0,043 m

Connectable conductor cross section fine-strand without cable end sleeve	1.5 - 35 mm <sup>2</sup>
Connectable conductor cross section fine-strand with cable end sleeve	1.5 - 35 mm <sup>2</sup>
Connectable conductor cross section solid-core	Unknown
Connectable conductor cross section multi-wired	1.5 - 50 mm <sup>2</sup>
Rated current I <sub>n</sub>	320 A
Rated voltage	1500 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Not applicable
Number of levels	1
Number of clamp positions per level	4
Mounting method	DIN rail (top hat rail) 35 mm
Material insulation body	Thermoplastic
Operating temperature	-25 - 80 °C
Inflammability class of insulation material according to UL94	-
Width	30 mm
Height	43 mm
Depth	49 mm
Explosion-tested version 'Ex e'	No
Closing plate required	No
Colour	Grey
Internally connected stages	Yes

