



Zdjęcie jest reprezentatywne

Eaton 266614

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, lockable

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	266614
EAN	4015082666149
PRODUCT LENGTH/DEPTH	230 mm
PRODUCT HEIGHT	130 mm
PRODUCT WIDTH	230 mm
PRODUCT WEIGHT	1.785 kg
COMPLIANCES	IEC UL/CSA RoHS conform
CERTIFICATIONS	CSA (Class No. 1437-01) UL489 UL listed CE marking IEC60947 UL (File No. E140305) CSA (File No. 22086) UL (Category Control Number DIHS) CSA certified CSA-C22.2 No. 5-09
MODEL CODE	NZM4-XTVD

Delivery program

TYPE	<ul style="list-style-type: none">• Accessory• Door coupling rotary handle
-------------	---

FEATURES	Lockable Standard: black / gray
-----------------	------------------------------------

SPECIAL FEATURES	<ul style="list-style-type: none">• Door coupling rotary handle for operating the switch through a closed control panel door• External warning plate/designation label can be clipped on.• Complete including rotary drive and coupling parts• Extension shaft additionally required.
-------------------------	--

FRAME	NZM4
--------------	------

FITTED WITH:	Padlock
---------------------	---------

SUITABLE FOR	Power circuit breaker Switch disconnecter
---------------------	--

USED WITH	NZM4(-4), N(S)4(-4)
------------------	---------------------

Technical Data - Mechanical

COLOR	Black
--------------	-------

COVER/DOOR TYPE	Door interlock can be modified in the unlocked ON position Door interlock not defeated in the locked OFF and ON positions Door can be opened in OFF Door interlock can be modified such that it can be defeated from the outside using a screwdriver
------------------------	---

DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	IP66 4X. 12
---	----------------

LOCK NUMBER	Single lockable
--------------------	-----------------

LOCKING FACILITY	Lockable on the 0 position on the handle using up to 3 padlocks With door interlock
-------------------------	--

SPECIAL FEATURES	<ul style="list-style-type: none">• Door coupling rotary handle for operating the switch through a closed control panel door• External warning plate/designation label can be clipped on.• Complete including rotary drive and coupling parts• Extension shaft additionally required.
-------------------------	--

Design verification as per IEC/EN 61439

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Do pobrania

INSTRUKCJE MONTAŻU	eaton-circuit-breakers-nzm4-xt-door-coupling-ii01210003z.pdf
MODELE MCAD	DA-CS-nzm4_xtvd DA-CD-nzm4_xtvd
RYSUNKI	eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-007.eps eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-011.eps eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-005.eps

**10.12
ELECTROMAGNETIC
COMPATIBILITY**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL
FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

NAZWA PROJEKTU:

NUMER PROJEKTU:

PRZYGOTOWANE PRZEZ:

DATA:

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

Najnowsze informacje o produktach i wsparciu znajdują się na naszych mediach społecznościowych.